

KÄRCHER

makes a difference



EFFICIENT AND CONFIGURABLE.

Sweeping, scrubbing and vacuuming for large areas.

PROFESSIONAL | B 150 R BP

Race into efficiency with the B 150.

The B 150 R can cover up to 64,580 ft²/hr making this one impressively productive scrubber. Although it can cover large areas quickly, we made sure that it has great visibility for safety. Our KIK operating system and the color coded controls make operation simple and intuitive. KIK allows managers to control what functions and settings their employees can use and adjust.



1 Advanced model features all-wheel drive

- Clean ramps with grades up to 18%
- Features a unique all-wheel brake system for safety

2 Maximum control

- Utilize the large color LCD screen to adjust everything to your needs including contact pressure, water volume, brush speed, etc.

3 Let the machine do the work

- Auto tank-rinsing and auto-fill come standard to allow the operator to do other tasks while rinse and fill are taking place

4 Extremely maneuverable

- The short and narrow design makes the machine very maneuverable. Ideal for angled interiors, and provides good line-of-site. This makes cleaning faster, more efficient and safer

TECHNICAL DATA AND EQUIPMENT

		B 150 R			
+ brush head		R 75	D 75	R 90	D 90
TECHNICAL SPECIFICATIONS					
Working width, brushes	in	30	30	35	35
Working width, vacuuming	in	37	37	42	42
Fresh / dirty water tank capacity	gal	40/40	40/40	40/40	40/40
Productivity (Theoretical / Practical)	ft ² /hr	48,438/34,445	48,438/34,445	58,125/40,903	58,125/40,903
Water flow max.	gpm	2	2	2	2
Brush speed	rpm	600-1300	180	600-1300	180
Power consumption, (ecoefficiency mode)	W	2,800	2,800	2,800	2,800
Power consumption, traction motor, max.	W	2,500	2,500	2,500	2,500
Driving and cleaning speed	mph	3.7	3.7	3.7	3.7
Weight (with battery)	lbs	959-1,146	959-1,146	959-1,146	959-1,146
Dimensions (L x W x H) w/o attachments	in	65 x 31 x 56	65 x 31 x 56	65 x 31 x 56	65 x 31 x 56
Voltage supply	V	36	36	36	36
Waste container	gal	2	-	2.5	-

EQUIPMENT

Order No.	Description
9.841-286.0	B 150 R Bp, 36V ride-on auto scrubber with 360 Ah batteries. Scrub deck sold separately
9.841-287.0	B 150 R Bp SB, 36V ride-on auto scrubber with 360 Ah batteries and dual side brushes. Scrub deck sold separately
9.841-288.0	B 150 R Bp Advanced, 36V ride-on auto scrubber with 360 Ah batteries. Scrub deck sold separately
9.841-289.0	B 150 R Bp SB Advanced, 36V ride-on auto scrubber with 360 Ah batteries. Scrub deck sold separately
9.841-290.0	B 150 R Bp, with R 75 scrub deck 36V/30" ride-on auto scrubber with 360 Ah batteries
9.841-291.0	B 150 R Bp, with R 75 scrub deck 36V/30" ride-on auto scrubber with 312 Ah AGM batteries
9.841-294.0	B 150 R Bp SB, with R 75 scrub deck 36V/30" ride-on auto scrubber with 360 Ah batteries and dual side brushes.
9.841-295.0	B 150 R Bp SB, with R 75 scrub deck 36V/30" ride-on auto scrubber with 312 Ah AGM batteries and dual side brushes.
9.841-292.0	B 150 R Bp, with R 90 scrub deck 36V/36" ride-on auto scrubber with 360 Ah batteries.
9.841-293.0	B 150 R Bp, with R 90 scrub deck 36V/36" ride-on auto scrubber with 312 Ah AGM batteries.
9.841-296.0	B 150 R Bp SB, with R 90 scrub deck 36V/36" ride-on auto scrubber with 360 Ah batteries and dual side brushes.
9.841-297.0	B 150 R Bp SB, with R 90 scrub deck 36V/36" ride-on auto scrubber with 312 Ah AGM batteries and dual side brushes.

ACCESSORIES

Order No.	Description
■ 4.777-402.0	Suction bar, straight, 37" (940mm) - standard on machines with R 75 scrub deck
■ 4.777-403.0	Suction bar, straight, 42" (1060mm) - standard on machines with R 90 scrub deck
■ 8.622-842.0	Battery, 6V, 360 Ah, low-maintenance
■ 8.629-184.0	Battery, 6V, 312 Ah, AGM low-maintenance
■ 8.628-408.0	Battery charger, 36V, 36A, 115V. For use with 8.622-842.0
■ 8.600-015.0	Battery charger, 36V, 21A, 115V. For use with 8.622-184.0 AGM.
□ 2.642-058.0	Spray Suction Kit - for Cleaning Areas Not Easily Accessed by Machine (field installation required)
□ 6.435-733.0	Back Wheel Without Profile - reduces wheel marks on sensitive, while floors (field installation required)
□ 4.444-015.0	Suction Hose Accessories - 10.5 ft/3.25 m for clean-up of water in corners or containers (field installation required)
□ 4.035-516.0	B360° Warning Beacon (field installation required)
□ 4.777-412.0	Suction bar, curved, 37" (940mm) - for use on machines with D 75 scrub deck
□ 4.777-413.0	Suction bar, curved, 42" (1060mm) - for use on machines with D 90 scrub deck
□ 6.273-215.0	Standard, Squeegee, Blue (2 required)
□ 6.273-209.0	Oil Resistant Squeegee, Brown
□ 6.273-206.0	Oil Resistant Squeegee, Streak Free, Brown
□ 2.641-811.0	Cleaning agent dosing system DS 3 - Can be directly connected to the main water supply; the fresh water tank is filled with the mixture of water and cleaning agent. Also in connection with the ABS filling system.
□ 6.435-810.0	Front tires, traction - with V profile and tire compound with especially good traction properties. Oil-proof.
□ 6.951-073.0	(1) Replacement Side Brush - only for use with R-type scrub decks

■ Included □ Optional

Please contact us for more information:

North America

4555 Airport Way
Denver, CO 80239
U.S.A.

Phone 800-456-6649
Fax 303-738-2818

www.karcher.com/us

Canada

6535 Millcreek Drive
Unit 67
Mississauga, ON L5N 2M2
Canada

Phone 905-672-8233
Fax 905-672-3155

www.karcher.ca